IN THE CLAIMS:

The following are the currently pending claims and proposed. (All claims listed)

1. (Cancelled)	
2. (Currently Amended)	The method of claim [[4]] $\underline{3}$ further comprising storing each of the
set of instructions into a parti	cular one of a set of bins in the instruction cache that corresponds to
the particular one of the set o	f execution units that the instruction requires.
3. (Currently Amended)	The method of claim 1 further comprising A method for executing
a set of instructions in a proc	essor, comprising:
decoding the set of in	structions;
renaming a set of regi	sters of a particular one of the set of instructions, prior to steering
the set of instructions into the	instruction cache;
steering each decoded	l instruction of the set of instructions into an instruction cache so as
to store each of said decoded	instructions at a location in said instruction cache based on a
particular one of a set of exec	cution units that the decoded instruction requires; and
issuing each of the se	t of instructions from said instruction cache to a particular one of
said set of execution units.	
4. (Original) The method o	f claim 3 further comprising scheduling a particular one of the set of

DC01 533393v 1

instructions if the particular one of the set of instructions is found in the instruction cache.

5. (Original) The method of claim 4 further comprising executing the particular one of the set		
of instructions that is scheduled, using the particular one of the set of execution units that the		
particular one of the set of instructions requires.		
6. (Original) The method of claim 3 further comprising fetching a particular one of the set of		
instructions from a memory device if the particular one of the set of instructions is not found in		
the instruction cache.		
7. (Cancelled)		
8. (Currently Amended) The method of claim [[7]] 9 further comprising storing each of the		
set of instructions into a particular one of a set of bins in the instruction cache that corresponds to		
the particular one of the set of execution units that the instruction requires.		
9. (Currently Amended) The method of claim 7-further comprising A method for executing		
a set of instructions in a processor, comprising:		
decoding the set of instructions;		
renaming a set of registers of a particular one of the set of instructions, prior to		
scheduling the set of instructions;		
scheduling the set of instructions to avoid pipeline stalls; and		
steering each of the set of instructions into an instruction cache so as to store each of said		
instructions at a location in said instruction cache based on a particular one of a set of execution		

DC01 533393v 1

units that the instruction requires after the scheduling operation.

10. (Original) The method of claim 9 further comprising executing the particular one of the set		
of instructions, using the particular one of the set of execution units that the instruction requires,		
if the particular one of the set of instructions is found in the instruction cache.		
11. (Original) The method of claim 9 further comprising fetching a particular one of the set of		
instructions from a memory device if the particular one of the set of instructions is not found in		
the instruction cache.		
12. (Cancelled)		
13. (Currently Amended) The method of claim [[12]] 14 further comprising storing each of		
the set of instructions into a particular one of a set of bins in the instruction cache that		
corresponds to the particular one of the set of execution unit clusters that the instruction requires.		
14. (Currently Amended) The method of claim 12 further comprising A method for		
executing a set of instructions in a processor, comprising:		
decoding the set of instructions;		
renaming a set of registers of a particular one of the set of instructions, prior to steering		
the set of instructions into the instruction cache;		
steering at a first time each of the set of instructions into an instruction cache so as to		
store each of said instructions at a location in said instruction cache based on a particular one of a		
set of execution unit clusters that the instruction requires; and		
issuing each of the set of instructions from said instruction cache to a particular one of		
said set of execution unit clusters. DC01 533393v 1		

- 15. (Original) The method of claim 14 further comprising scheduling a particular one of the set of instructions if the particular one of the set of instructions is found in the instruction cache.
 - 16. (Original) The method of claim 15 further comprising steering, at a second time, the particular one of the set of instructions that is scheduled into one of a set of execution units, within the particular one of the set of execution unit clusters, that the instruction requires.
 - 17. (Original) The method of claim 16 further comprising executing the particular one of the set of instructions that is steered the second time, using the one of the set of execution units that the particular one of the set of instructions requires.
 - 18. (Original) The method of claim 14 further comprising fetching a particular one of the set of instructions from a memory device if the particular one of the set of instructions is not found in the instruction cache.
 - 19. (Cancelled)
 - 20. (Currently Amended) The processor of claim [[19]] 21 wherein the instruction cache includes a set of bins, each of the set of bins corresponding to a particular one of a set of execution units that a particular one of the set of instructions requires.
 - 21. (Currently Amended) The processor of claim 19 further comprising, A processor, comprising:

 DC01 533393y 1

an instruction cache;		
a crossbar to receive instructions from a memory device and coupled to the instruction		
cache to steer each of a set of instructions into the instruction cache so as to store each of said		
instructions at a location in said instruction cache based on a particular one of a set of execution		
units that the instruction requires, wherein each of the set of instructions are to be issued from		
said instruction cache to a particular one of said set of execution units; and		
a register renaming unit coupled to the crossbar, to eliminate false data dependencies.		
22. (Original) The processor of claim 21 further comprising a set of reservation stations, each of		
the set of reservation stations coupled to a corresponding one of the set of bins in the instruction		
cache, to schedule the set of instructions to avoid pipeline stalls.		
23. (Original) The processor of claim 21 further comprising a reservation station, coupled to the		
register renaming unit, to schedule the set of instructions to avoid pipeline stalls.		
24. (Cancelled)		
25. (Currently Amended) The processor of claim [[24]] 26 wherein the instruction cache		
includes a set of bins, each of the set of bins corresponding to a particular one of a set of		
execution unit clusters that a particular one of the set of instructions requires.		
26. (Currently Amended) The processor of claim 24 further comprising A processor,		
comprising:		

an instruction cache;

DC01 533393v 1

a first crossbar to receive instructions from a memory device coupled to the instruction cache to steer each of a set of instructions into the instruction cache so as to store each of said instructions at a location in said instruction cache based on a particular one of a set of execution unit clusters that the instruction requires, wherein each of the set of instructions are to be issued from said instruction cache to a particular one of said set of execution unit clusters; and

a register renaming unit, coupled to the first crossbar, to eliminate false data dependencies.

- 27. (Original) The processor of claim 26 further comprising a set of reservation stations, each of the set of reservation stations coupled to a corresponding one of the set of bins in the instruction cache, to schedule the set of instructions to avoid pipeline stalls.
- 28. (Original) The processor of claim 27 further comprising a set of second crossbars, each of the set of second crossbars coupled to a corresponding one of the set of reservation stations, to steer, at a second time, each of the set of instructions to a particular one of a set of execution units, within the particular one of the set of execution unit clusters, that the instruction requires.
- 29. (New) A system, comprising:
 - a memory device to store a plurality of instructions;
 - a processor including

an instruction cache;

a crossbar to receive instructions from the memory device and coupled to the instruction cache to steer each of a set of instructions into the instruction cache so as to store each of said instructions at a location in said instruction cache based on a particular one of a set DC01 533393v 1

of execution units that the instruction requires, wherein each of the set of instructions are to be issued from said instruction cache to a particular one of said set of execution units; and a register renaming unit coupled to the crossbar, to eliminate false data dependencies.

- 30. (New) The system of claim 29 wherein the instruction cache includes a set of bins, each of the set of bins corresponding to a particular one of a set of execution units that a particular one of the set of instructions requires.
- 31. (New) The system of claim 29 wherein said processor further includes a set of reservation stations, each of the set of reservation stations coupled to a corresponding one of the set of bins in the instruction cache, to schedule the set of instructions to avoid pipeline stalls.
- 32. (New) The system of claim 29 further comprising a reservation station, coupled to the register renaming unit, to schedule the set of instructions to avoid pipeline stalls.
- 33. (New) A system, comprising:
 - a memory device to store a plurality of instructions;
 - a processor including

an instruction cache;

a first crossbar to receive instructions from a memory device coupled to the instruction cache to steer each of a set of instructions into the instruction cache so as to store each of said instructions at a location in said instruction cache based on a particular one of a set

DC01 533393v 1

of execution unit clusters that the instruction requires, wherein each of the set of instructions are to be issued from said instruction cache to a particular one of said set of execution unit clusters; a register renaming unit, coupled to the first crossbar, to eliminate false data dependencies.

- 34. (New) The system of claim 33 wherein the instruction cache includes a set of bins, each of the set of bins corresponding to a particular one of a set of execution unit clusters that a particular one of the set of instructions requires.
- 35. (New) The system of claim 33 wherein the processor further includes a set of reservation stations, each of the set of reservation stations coupled to a corresponding one of the set of bins in the instruction cache, to schedule the set of instructions to avoid pipeline stalls.
- 36. (New) The system of claim 33 wherein the processor further includes a set of second crossbars, each of the set of second crossbars coupled to a corresponding one of the set of reservation stations, to steer, at a second time, each of the set of instructions to a particular one of a set of execution units, within the particular one of the set of execution unit clusters, that the instruction requires.